

**BORO****Et Único Experto  
en Mangueras**

## INDUSTRIAL

Code	Inside diameter (Inch)		Weight Kg/Met		Work Pressure To 74.3°F	Bursting pressure to 73.4°C
	Min	Max	to	Burstin		
INE.1/4	0.244	0.256	0.026	0.030	90	270
INE.5/16	0.304	0.320	0.034	0.040	86	260
INE.3/8	0.360	0.380	0.049	0.055	83	250
INE.1/2	0.475	0.505	0.078	0.085	66	200
INE.5/8	0.595	0.630	0.120	0.130	63	190
INE.3/4	0.715	0.755	0.155	0.170	60	180
INE.1"	0.965	1.010	0.295	0.310	46	140
INE.1 1/4	1.225	1.255	0.440	0.470	43	130
INE.1 1/2	1.460	1.510	0.600	0.640	40	120
INE.2"	1.960	2.010	1.050	1.100	36	110

**Work Temperature:** Min: 50°F - Max: 95°F**Guarantee:** 5 Years**Hardness Shore to 73.4°F:** 90 (Min) - 93 (Max)

Presentations:	Packing	Diameter	Lenght	Unit	Unit / Packing	Max. Stowage
Roll:	Strench Wrap	1/4, 5/16, 3/8, 1/2, 5/8, 3/4 y 1	100	M	1	7
	Strench Wrap	1 1/4, 1 1/2 y 2	50	M	1	7

**Notes:**

Guarantee only apply in manufacturing defects

**How to extend product life:**

Do not use cutting products or chemicals

After every use roll up and keep it safe

Do not use for transport chemicals or abrasive fluids

**Corporativo Boro S.A. de C.V**Tel: (0133) 3834 0659 • Lada: 01800 700 BORO (2676)  
Las Lomas 144 • Fracc. Los Robles • C.P. 45134  
Zapopan, Jalisco, México[www.boro.mx](http://www.boro.mx)