



*El Único Experto
en Mangueras*

GREEN TISSUE

Code	Inside diameter (Inches)		Weight Kg/Metro		Threads per Inch		Work Pressure
	Min	Max	Min	Max	Min	Max	Trabajo
NTV.1/2	0.475	0.505	0.096	0.102	3.5	4	86
LTV.1/2	0.475	0.505	0.096	0.102	3.5	4	86
TV.5/8	0.595	0.630	0.145	0.156	3.5	4	80
TV.3/4	0.715	0.755	0.218	0.230	3.5	4	73
TV.1"	0.965	1.010	0.380	0.400	3.5	4	66

Adhesion to connection-hose in Kp: 1/2= 90 5/8=127 3/4=150

Work Temperature: Min: 50°F - Max: 95°F

Guarantee: 5 Years

Hardness Shore to 73.4°F: 90 (Min) - 93 (Max)

Tissue Kelos

Presentation:	Diameter	Lenght	Unit	Unit / Packing	Max. Stowage	Packing
Roll:	1/2	100	Mts	1	7	Strench Wrap
	5/8	100	Mts	1	7	Strench Wrap
	3/4	100	Mts	1	7	Strench Wrap
	1	100	Mts	1	7	Strench Wrap
Piece:	1/2	10, 15, 20, 25 y 30	Mts	3	5	Bag
	1/2	25, 50, 75 ,100,150 y 200	Ft	3	5	Bag
	5/8	10, 15, 20, 25 y 30	Mts	3	5	Bag
	5/8	25, 50, 75 ,100,150 y 200	Ft	3	5	Bag
	3/4	10, 15, 20, 25 y 30	Mts	3	5	Bag

Notes:

Guarantee only apply in manufacturing defects

How to extend product life:

Do not use cutting products or chemicals
After every use roll up and keep it safe
Do not use for transport chemicals or abrasive fluids