

**BORO****El Único Experto
en Mangueras**

TRAMAFLEX

Code	Inside diameter (Inches)		Weight Kg/Met		Hilos por Pulgada		Work Pressure To 73.4°F	Presión de Reventamiento a 23°C
	Min	Max	Min	Max	N	Max		
PF.1/4	0.244	0.256	0.068	0.075		5.5	2	620
PF.5/16	0.304	0.320	0.078	0.085		5.5	1	550
PF.3/8	0.360	0.380	0.092	0.098		5.5	1	475
PF.1/2	0.475	0.505	0.147	0.157		5	1	420
PF.3/4	0.715	0.755	0.250	0.270	3	4	1	300
PF.1"	0.965	1.010	0.448	0.468	3	4	8	260

Adhesion to connection-hose in Kp: 5

Work Temperature: Min: 50°F - Max: 95°F

Guarantee: 5 Years

Hardness Shore to 73.4°F 90 (Min) - 93 (Max)

Tissue Kelos

Presentations:	Diameter	Length	Unit	Unit / Packing	Max. Stowage	Packing
Roll:	1/4	100	M	1	7	Strench Warp
	5/16	100	M	1	7	Strench Warp
	3/8	100	M	1	7	Strench Warp
	1/2	100	M	1	7	Strench Warp
	3/4	50	M	1	5	Strench Warp
	1"	50	M	1	5	Strench Warp

Notes:

Guarantee only apply in manufacturing defects

How to extend product life:

Do not use cutting products or chemicals

After every use roll up and keep it safe

Do not use for transport chemicals or abrasive fluids

Corporativo Boro S.A. de C.V

Tel: (0133) 3834 0659 • Lada: 01800 700 BORO (2676)
Las Lomas 144 • Fracc. Los Robles • C.P. 45134
Zapopan, Jalisco, México

www.boro.mx

