



**Et Único Experto
en Mangueras**

POLY AIRE

| Code | Inside diameter | | Weight | | Threads per inch | | Work pressure | Bursting pressure to 74.3°F |
|--------|-----------------|-------|--------|-------|------------------|-----|---------------|--------------------------------|
| | Min | Max | Min | Max | Min | Max | To 74.3 °F | |
| PA.1/4 | 0.244 | 0.256 | 0.115 | 0.123 | 5 | 5.5 | 216 | 650 |

Adhesión of layers (Kp): 5

Work Temperature: Min: 50°F - Max: 95°F

Guarantee: 3 years

Hardness Shore to 73.4°F: 90 (Min) - 93 (Max)

Tissue **Kelos**

| Presentations: | Diameter | Lenght | Unit | Unit / Packing | Max. Stowage | Packing |
|----------------|----------|----------------|------|----------------|--------------|--------------|
| Roll: | 1/4 | 100 | M | 1 | 7 | Strench wrap |
| Piece: | 1/4 | 5, 10, 15 y 20 | M | 3 | 5 | Bag |

Notes:

Guarantee only apply in manufacturing defects

How to extend product life:

Do not use cutting products or chemicals

After every use roll up and keep it safe

Do not use for transport chemicals or abrasive fluids

Corporativo Boro S.A. de C.V

Tel: (0133) 3834 0659 • Lada: 01800 700 BORO (2676)
Las Lomas 144 • Fracc. Los Robles • C.P. 45134
Zapopan, Jalisco, México

www.boro.mx

