



## KELOS PROFESSIONAL USE

| Code   | Inside diameter (Inch) |       | Weight Kg/Metro |       | Threads per inch |     | Work Pressure to 73.4 °F | Bursting pressure to 73.4°c |
|--------|------------------------|-------|-----------------|-------|------------------|-----|--------------------------|-----------------------------|
|        | Min                    | Max   | Min             | Max   | Min              | Max |                          |                             |
| KP.1/2 | .475                   | .505  | 0.128           | 0.135 | 5                | 5.5 | 100 PSI                  | 300 PSI                     |
| KP.5/8 | .595                   | .630  | 0.170           | 0.180 | 5                | 5.5 | 83 PSI                   | 250 PSI                     |
| KP.3/4 | .715                   | .755  | 0.245           | 0.256 | 5                | 5.5 | 73 PSI                   | 220 PSI                     |
| KP.1"  | .965                   | 1,010 | 0.400           | 0.420 | 5                | 5.5 | 66 PSI                   | 200 PSI                     |

Adhesion to connection-hose in Kp:

1/2=100 5/8=136 3/4=160

Work Temperature: Min: 5°C - Max: 60°C

Guarantee: 4 Years

Hardness Shore to 73.4°F 90 (Min) - 93 (Max)

Tissue ☐ Kelos ☒

| Presentation: | Diameter | Lenght              | Unit | Unit / Packing | Max. Stowage | Packing      |
|---------------|----------|---------------------|------|----------------|--------------|--------------|
| Roll:         | 1/2      | 100                 | Mts  | 1              | 7            | Strench Wrap |
|               | 5/8      | 100                 | Mts  | 1              | 7            | Strench Wrap |
|               | 3/4      | 100                 | Mts  | 1              | 7            | Strench Wrap |
|               | 1"       | 100                 | Mts  | 1              | 7            | Strench Wrap |
| Piece:        | 1/2      | 10, 15, 20, 25 y 30 | Mts  | 3              | 5            | Bag          |
|               | 5/8      | 10, 15, 20, 25 y 30 | Mts  | 3              | 5            | Bag          |
|               | 3/4      | 10, 15, 20, 25 y 30 | Mts  | 3              | 5            | Bag          |

### Notes:

Guarantee only apply in manufacturing defects

### How to extend product life:

Do not use cutting products or chemicals

After every use roll up and keep it safe

Do not use for transport chemicals or abrasive fluids

**Corporativo Boro S.A. de C.V**

Tel: (0133) 3834 0659 • Lada: 01800 700 BORO (2676)

Las Lomas 144 • Fracc. Los Robles • C.P. 45134

Zapopan, Jalisco, México

[www.boro.mx](http://www.boro.mx)

